

IN THE CLAIMS

Kindly cancel claims 4, 8 and 15, without prejudice, and amend claims 1, 5, 6 and 13 as shown in the attached claim listing:

1. (currently amended) Apparatus for producing a stereoscopic image comprising display means for displaying an image and user control means for controlling ~~at least one~~ two stereoscopic ~~parameter~~ parameters of the image displayed by the display means ; said user control means being a single control.
2. (original) Apparatus according to claim 1, said apparatus further comprising image deflection means overlying said display means.
3. (original) Apparatus according to claim 2, wherein said image deflection means is a lenticular screen.
4. (cancelled) Apparatus according to claim 1, wherein said user control means is a single control.
5. (currently amended) Apparatus according to claim ~~4~~, 1 wherein said single control is a knob.
6. (currently amended) Apparatus according to claim ~~4~~, 1 wherein said single control is an icon.
7. (original) Apparatus according to claim 1, said apparatus further comprising a remote device communicating with said user control means.

8. (canceled) Apparatus according to claim 1, wherein said user control means controls two stereoscopic parameters.
9. (original) Apparatus according to claim 1, wherein a stereoscopic parameter is the perceived depth of the image.
10. (original) Apparatus according to claim 1, wherein a stereoscopic parameter is the perceived position of the image relative to the display means.
11. (previously presented) Apparatus according to claim 9, wherein said apparatus is arranged so that when said user control means is at a minimum the perceived depth of the image is at a minimum and as said single control moves from a minimum to a maximum the perceived depth of the image increases.
12. (original) Apparatus according to claim 1, wherein said display means is a liquid crystal display.
13. (currently amended) A method for producing a stereoscopic image comprising displaying an image and controlling ~~at least one~~ two stereoscopic ~~parameter~~ parameters of the image in response to a user input via a single control.
14. (original) A method according to claim 13, wherein said image is autostereoscopic.
15. (cancel) A method according to claim 13, wherein said user input is via a single control.
16. (original) A method according to claim 13, wherein a stereoscopic parameter is the perceived depth of the image.

17. (original) A method according to claim 13, wherein a stereoscopic parameter is the perceived position of the image relative to its display.

18. (previously presented) A computer program product, for carrying out method claim 13.